12B4-A
LOW-MU TRIODE

9-PIN MINIATURE TYPE

Intended for use in equipment having series heater-string arrangement

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

	Series	*Parallel*	
Heater arrangement			
Voltage	12.6	6.3	ac or dc volts
Current	0.300	0.600	amp
Warm-up time (Average)	-	11	sec

For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.

Direct Interelectrode Capacitances (Approx.):°

Grid to plate	4.8	μμf
Grid to cathode and heater	5	μμf
Plate to cathode and heater	1.5	μμf

Characteristics, Class A_1 Amplifier:

Plate Voltage	150	volts
Grid Voltage	-17.5	volts
Amplification Factor	6.5	
Plate Resistance (Approx.)	1030	ohms
Transconductance	6300	μmhos
Plate Current	34	ma
Grid Voltage (Approx.) for plate current of 200 μamp	-32	volts
Plate Current for grid voltage of -23 volts	9.6	ma

Mechanical:

Mounting Position	Any
Maximum Overall Length	2-5/8"
Maximum Seated Length	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip)	2" ± 3/32"
Maximum Diameter	7/8"
Bulb	T-6-1/2
Base	Small-Button Noval 9-Pin (JETEC No.E9-1)
Basing Designation for BOTTOM VIEW	9AG

Pin 1 - Cathode
Pin 2 - Grid
Pin 3 - Heater Mid-Tap
Pin 4 - Heater
Pin 5 - Heater



Pin 6 - No Connection
Pin 7 - Grid
Pin 8 - No Connection
Pin 9 - Plate

° With external shield JETEC No.315 connected to cathode.

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

12B4-A

12B4-A
LOW-MU TRIODE

AMPLIFIER - Class A_1

Maximum Ratings, *Design-Center Values*:

PLATE VOLTAGE	550	max.	volts
GRID VOLTAGE:			
Negative bias value	50	max.	volts
PLATE DISSIPATION	5.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater positive with respect to cathode	200▲	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:			
For fixed-bias operation	0.47	max.	megohm
For cathode-bias operation	2.2	max.	megohms

VERTICAL DEFLECTION AMPLIFIER

Maximum Ratings, *Design-Center Values Except as Noted*:

For operation in a 525-line, 30-frame system□

DC PLATE VOLTAGE	550	max.	volts
PEAK POSITIVE-PULSE PLATE VOLTAGE (Absolute maximum)#	1000■	max.	volts
PEAK NEGATIVE-PULSE GRID VOLTAGE	250	max.	volts
CATHODE CURRENT:			
Peak	105	max.	ma
Average	30	max.	ma
PLATE DISSIPATION	5.5	max.	watts
PEAK HEATER-CATHODE VOLTAGE:			
Heater negative with respect to cathode	200	max.	volts
Heater negative with respect to cathode	200▲	max.	volts

Maximum Circuit Values:

Grid-Circuit Resistance:			
For cathode-bias operation	2.2	max.	megohms

▲ The dc component must not exceed 100 volts.

□ As described in "Standards of Good Engineering Practice Concerning Television Broadcast Stations", Federal Communications Commission.

This rating is applicable where the duration of the voltage pulse does not exceed 15 per cent of one vertical scanning cycle. In a 525-line, 30-frame system, 15 per cent of one vertical scanning cycle is 2.5 milliseconds.

■ Under no circumstances should this absolute value be exceeded.

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY